

**XLPE insulated steel wire armoured control cable, 450/750V
 CU/XLPE/PVC/SWA/PVC**

No.x cross-sectional area of conductor	Nominal stranding of conductor	Insulation thickness	Outer sheath thickness	Approx. overall diameter	Approx. weight
No.xmm²	No./mm	mm	mm	mm	kg/km
7x1.5	7/0.53	0.6	1.5	16.8	543.7
7x2.5	7/0.67	0.7	1.5	18.6	684.8
7x4.0	7/0.85	0.7	1.7	20.5	848.8
7x6.0	7/1.04	0.7	1.7	22.7	1156.7
7x10.0	7/1.35	0.7	1.7	25.1	1524.5
12x1.5	7/0.53	0.6	1.5	20	740.1
12x2.5	7/0.67	0.7	1.7	23.6	1098.5
12x4.0	7/0.85	0.7	1.7	25.7	1359.8
19x1.5	7/0.53	0.6	1.7	23.5	1084.7
19x2.5	7/0.67	0.7	1.7	26.5	1422.4
19x4.0	7/0.85	0.7	1.7	29.2	1810.7
27x1.5	7/0.53	0.6	1.7	26.7	1365.6
27x2.5	7/0.67	0.7	1.7	31.6	1907.6

*The information in this datasheet is for reference only and is subject to change without notice or liability.